

AV Products Australia

Spec File

DSPPA DSP6606, DSP6608 Active Wall Speakers

Features

- High performance
- Compact
- 2 Inputs
- Stereo/Mono

Application

- Conferences /Meeting Rooms
- Bars/Restaurant's
- Class Rooms

Description

Two way active speakers with 5" and 6.5" drivers, Sold as pairs 1 powered box and 1 slave.



Manufactured By
DSPPA

AV Products Australia
PO Box R592
Royal Exchange 1225
Phone: +61 2 9241 1884
Web: www.avpau.com
E-mail: slaes@avpau.com

Model	DSP6606
Driver Unit	5 x 1, 1" x 1
Built-in Amplifier	2x30w
Bluetooth input	
Power supply	AC 100-240V/220V 50/60Hz
Freq.Response	20Hz-20KHz
Max SPL	≥104dB
Input Sensitivity	Line:300mV,MIC:40mV @XLR;300mv@6.3
Material	Housing:ABS, Black Grille:Aluminum,Black,
Unit Size	176x147x255mm
Weight	2.1kg

AV Products

Australia

Model No.		DSP6608
Line	Input Impedance	>10K Ω
	Input Sensitivity	500mV
	Frequency	50Hz-20KHz
	Distortion	\leq 0.1%
	Signal to Noise Ratio	\geq 80dB
MIC	Input Impedance	>600 Ω
	Input Sensitivity	2.5mV
	Frequency	50Hz-20KHz
	Distortion	\leq 1%
	Signal to Noise Ratio	\geq 65dB
Pre-out	Input Impedance	<50 Ω
	Output	1.0V
	Frequency	50Hz-20KHz
	Distortion	\leq 0.1%
	Signal to Noise Ratio	\geq 80dB
Output Power	Rated Output	40W + 40W/8 Ω
	Frequency	50Hz-20KHz
	Distortion	\leq 0.5%
	Signal to Noise Ratio	\geq 80dB
Speaker Drivers	Max Sound Pressure	\geq 100dB
	Bass Driver Capacity	30W/8 Ω
	Tweeter Capacity	15W/8 Ω
	Frequency	50Hz-20KHz
	Distortion	\leq 0.1%
Connections	Line In	RCA、3.5mm
	MICIn	Balanced 、 Unbalanced 6.3mm
	Pre-out	RCA、3.5mm
	Right Channel output	Clamping Terminals (L,R)
Others	Power Supply	\sim 100-240V / 50/60Hz
	Circuit Protection	Included
	Packing Dimensions	590*275*390 mm
	Actual Dimensions (per speaker)	310*215*150 mm
	Net Weight	4.2kg